

**MetroPCS • Proposed Base Station (Site No. SF06190A)
704 Daffodil Court • Sunnyvale, California**

Statement of Hammett & Edison, Inc., Consulting Engineers

The firm of Hammett & Edison, Inc., Consulting Engineers, has been retained on behalf of MetroPCS, a personal wireless telecommunications carrier, to evaluate the base station (Site No. SF06190A) proposed to be located at 704 Daffodil Court in Sunnyvale, California, for compliance with appropriate guidelines limiting human exposure to radio frequency ("RF") electromagnetic fields.

Prevailing Exposure Standards

The U.S. Congress requires that the Federal Communications Commission ("FCC") evaluate its actions for possible significant impact on the environment. In Docket 93-62, effective October 15, 1997, the FCC adopted the human exposure limits for field strength and power density recommended in Report No. 86, "Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields," published in 1986 by the Congressionally chartered National Council on Radiation Protection and Measurements ("NCRP"). Separate limits apply for occupational and public exposure conditions, with the latter limits generally five times more restrictive. The more recent Institute of Electrical and Electronics Engineers ("IEEE") Standard C95.1-1999, "Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz," includes nearly identical exposure limits. A summary of the FCC's exposure limits is shown in Figure 1. These limits apply for continuous exposures and are intended to provide a prudent margin of safety for all persons, regardless of age, gender, size, or health.

The most restrictive limit for exposures of unlimited duration to radio frequency energy for several personal wireless services are as follows:

Personal Wireless Service	Approx. Frequency	Occupational Limit	Public Limit
Personal Communication ("PCS")	1,950 MHz	5.00 mW/cm ²	1.00 mW/cm ²
Cellular Telephone	870	2.90	0.58
Specialized Mobile Radio	855	2.85	0.57
[most restrictive frequency range]	30-300	1.00	0.20

Power line frequencies (60 Hz) are well below the applicable range of these standards, and there is considered to be no compounding effect from simultaneous exposure to power line and radio frequency fields.

General Facility Requirements

Base stations typically consist of two distinct parts: the electronic transceivers (also called "radios" or "cabinets") that are connected to the traditional wired telephone lines, and the passive antennas that send the wireless signals created by the radios out to be received by individual subscriber units. The transceivers are often located at ground level and are connected to the antennas by coaxial cables



HAMMETT & EDISON, INC.
CONSULTING ENGINEERS
SAN FRANCISCO

MP619A596_1
Page 1 of 4

**MetroPCS • Proposed Base Station (Site No. SF06190A)
704 Daffodil Court • Sunnyvale, California**

about 1 inch thick. Because of the short wavelength of the frequencies assigned by the FCC for wireless services, the antennas require line-of-sight paths for their signals to propagate well and so are installed at some height above ground. The antennas are designed to concentrate their energy toward the horizon, with very little energy wasted toward the sky or the ground. Along with the low power of such facilities, this means that it is generally not possible for exposure conditions to approach the maximum permissible exposure limits without being physically very near the antennas.

Computer Modeling Method

The FCC provides direction for determining compliance in its Office of Engineering and Technology Bulletin No. 65, "Evaluating Compliance with FCC-Specified Guidelines for Human Exposure to Radio Frequency Radiation," dated August 1997. Figure 2 attached describes the calculation methodologies, reflecting the facts that a directional antenna's radiation pattern is not fully formed at locations very close by (the "near-field" effect) and that the power level from an energy source decreases with the square of the distance from it (the "inverse square law"). The conservative nature of this method for evaluating exposure conditions has been verified by numerous field tests.

Site and Facility Description

Based upon information provided by Metro, including zoning drawings by DCI Pacific, dated September 17, 2004, it is proposed to mount three Kathrein Scala Model AP16-1850/065D/XP directional panel antennas on an existing 112¹/₂-foot PG&E lattice tower located near 704 Daffodil Court in Sunnyvale. The antennas would be mounted at an effective height of about 103 feet above ground and would be oriented with 2° downtilt toward 10°T, 110°T, and 240°T. The maximum effective radiated power in any direction would be 1,890 watts, representing six channels operating simultaneously at 315 watts each. Presently installed (or proposed) on the same tower are similar antennas for use by Cingular Wireless and by Sprint PCS, other wireless telecommunications carriers. Located on another PG&E lattice tower about 60 feet away are similar antennas for use by AT&T, another wireless telecommunications carrier. Transmitting facilities for those carriers are as follows:

Carrier	Antenna Model	Height	Maximum ERP
Cingular	EMS RR9017*	112 ft	1,500* watts
Sprint	EMS FR90-16-02DP	64	1,500*
AT&T	Andrew DB858DDH65	53	1,400

* Assumed for the purposes of this study.



HAMMETT & EDISON, INC.
CONSULTING ENGINEERS
SAN FRANCISCO

MP619A596_I
Page 2 of 4

**MetroPCS • Proposed Base Station (Site No. SF06190A)
704 Daffodil Court • Sunnyvale, California**

Study Results

For a person anywhere at ground, the maximum ambient RF exposure level due to the proposed Metro operation by itself is calculated to be 0.00076 mW/cm², which is 0.076% of the applicable public exposure limit. The maximum calculated cumulative level at any ground level location for the simultaneous operation of all four carriers is 0.42% of the public exposure limit; the maximum level at the second floor elevation of any nearby home[†] is 0.62% of the public exposure limit. It should be noted that these results include several “worst-case” assumptions and therefore are expected to overstate actual power density levels.

No Recommended Mitigation Measures

Since they are to be mounted on a PG&E tower, the Metro antennas are not accessible to the general public, and so no mitigation measures are necessary to comply with the FCC public exposure guidelines. It is presumed that PG&E already takes adequate precautions to ensure that there is no unauthorized access to its tower. To prevent exposures in excess of the occupational limit by authorized PG&E workers, it is expected that they will adhere to appropriate safety protocols adopted by that company.

Conclusion

Based on the information and analysis above, it is the undersigned’s professional opinion that the base station proposed by MetroPCS at 704 Daffodil Court in Sunnyvale, California, will comply with the prevailing standards for limiting public exposure to radio frequency energy and, therefore, will not for this reason cause a significant impact on the environment. The highest calculated level in publicly accessible areas is much less than the prevailing standards allow for exposures of unlimited duration. This finding is consistent with measurements of actual exposure conditions taken at other operating base stations.


[†] Located at least 40 feet away, based on aerial photographs from Terraserver.



MetroPCS • Proposed Base Station (Site No. SF06190A)
704 Daffodil Court • Sunnyvale, California

Authorship

The undersigned author of this statement is a qualified Professional Engineer, holding California Registration Nos. E-13026 and M-20676, which expire on June 30, 2005. This work has been carried out by him or under his direction, and all statements are true and correct of his own knowledge except, where noted, when data has been supplied by others, which data he believes to be correct.



William F. Hammett
William F. Hammett, P.E.

January 7, 2005



HAMMETT & EDISON, INC.
CONSULTING ENGINEERS
SAN FRANCISCO


MP619A596_1
Page 4 of 4

FCC Radio Frequency Protection Guide

The U.S. Congress required (1996 Telecom Act) the Federal Communications Commission ("FCC") to adopt a nationwide human exposure standard to ensure that its licensees do not, cumulatively, have a significant impact on the environment. The FCC adopted the limits from Report No. 86, "Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields," published in 1986 by the Congressionally chartered National Council on Radiation Protection and Measurements, which are nearly identical to the more recent Institute of Electrical and Electronics Engineers Standard C95.1-1999, "Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz." These limits apply for continuous exposures from all sources and are intended to provide a prudent margin of safety for all persons, regardless of age, gender, size, or health.

As shown in the table and chart below, separate limits apply for occupational and public exposure conditions, with the latter limits (in *italics* and/or dashed) up to five times more restrictive:

Frequency	Electromagnetic Fields (f is frequency of emission in MHz)					
Applicable Range (MHz)	Electric Field Strength (V/m)		Magnetic Field Strength (A/m)		Equivalent Far-Field Power Density (mW/cm ²)	
0.3 – 1.34	614	<i>614</i>	1.63	<i>1.63</i>	100	<i>100</i>
1.34 – 3.0	614	<i>823.8/f</i>	1.63	<i>2.19/f</i>	100	<i>180/f²</i>
3.0 – 30	1842/f	<i>823.8/f</i>	4.89/f	<i>2.19/f</i>	900/f ²	<i>180/f²</i>
30 – 300	61.4	<i>27.5</i>	0.163	<i>0.0729</i>	1.0	<i>0.2</i>
300 – 1,500	3.54√f	<i>1.59√f</i>	√f/106	<i>√f/238</i>	f/300	<i>f/1500</i>
1,500 – 100,000	137	<i>61.4</i>	0.364	<i>0.163</i>	5.0	<i>1.0</i>



Higher levels are allowed for short periods of time, such that total exposure levels averaged over six or thirty minutes, for occupational or public settings, respectively, do not exceed the limits, and higher levels also are allowed for exposures to small areas, such that the spatially averaged levels do not exceed the limits. However, neither of these allowances is incorporated in the conservative calculation formulas in the FCC Office of Engineering and Technology Bulletin No. 65 (August 1997) for projecting field levels. Hammett & Edison has built those formulas into a proprietary program that calculates, at each location on an arbitrary rectangular grid, the total expected power density from any number of individual radio sources. The program allows for the description of buildings and uneven terrain, if required to obtain more accurate projections.

RFR.CALC™ Calculation Methodology

Assessment by Calculation of Compliance with FCC Exposure Guidelines

The U.S. Congress required (1996 Telecom Act) the Federal Communications Commission ("FCC") to adopt a nationwide human exposure standard to ensure that its licensees do not, cumulatively, have a significant impact on the environment. The maximum permissible exposure limits adopted by the FCC (see Figure 1) apply for continuous exposures from all sources and are intended to provide a prudent margin of safety for all persons, regardless of age, gender, size, or health. Higher levels are allowed for short periods of time, such that total exposure levels averaged over six or thirty minutes, for occupational or public settings, respectively, do not exceed the limits.

Near Field.

Prediction methods have been developed for the near field zone of panel (directional) and whip (omnidirectional) antennas, typical at wireless telecommunications cell sites. The near field zone is defined by the distance, D, from an antenna beyond which the manufacturer's published, far field antenna patterns will be fully formed; the near field may exist for increasing D until some or all of three conditions have been met:

$$1) D > \frac{2h^2}{\lambda} \quad 2) D > 5h \quad 3) D > 1.6\lambda$$

where h = aperture height of the antenna, in meters, and
 λ = wavelength of the transmitted signal, in meters.

The FCC Office of Engineering and Technology Bulletin No. 65 (August 1997) gives this formula for calculating power density in the near field zone about an individual RF source:

$$\text{power density } S = \frac{180}{\theta_{BW}} \times \frac{0.1 \times P_{net}}{\pi \times D \times h}, \text{ in mW/cm}^2,$$

where θ_{BW} = half-power beamwidth of antenna, in degrees, and
 P_{net} = net power input to the antenna, in watts.

The factor of 0.1 in the numerator converts to the desired units of power density. This formula has been built into a proprietary program that calculates distances to FCC public and occupational limits.

Far Field.

OET-65 gives this formula for calculating power density in the far field of an individual RF source:

$$\text{power density } S = \frac{2.56 \times 1.64 \times 100 \times RFF^2 \times ERP}{4 \times \pi \times D^2}, \text{ in mW/cm}^2,$$

where ERP = total ERP (all polarizations), in kilowatts,
 RFF = relative field factor at the direction to the actual point of calculation, and
 D = distance from the center of radiation to the point of calculation, in meters.

The factor of 2.56 accounts for the increase in power density due to ground reflection, assuming a reflection coefficient of 1.6 ($1.6 \times 1.6 = 2.56$). The factor of 1.64 is the gain of a half-wave dipole relative to an isotropic radiator. The factor of 100 in the numerator converts to the desired units of power density. This formula has been built into a proprietary program that calculates, at each location on an arbitrary rectangular grid, the total expected power density from any number of individual radiation sources. The program also allows for the description of uneven terrain in the vicinity, to obtain more accurate projections.